

Safety Data Sheet

Section 1 - Chemical Product and Company Information

Product Name: Color Wall Purple Product Code: SCW-0900

Trade Name: SCW-0900 Purple

Manufactured by: Chemtrec

Smith Paint Products
2900 Fairview Park Drive
2200 Paxton Street
Falls Church, VA 22042-4513
Harrisburg, PA 17111
(800) 262-8200

(800) 466-8781

Emergency Hot Line: (800) 424-9300

Product Use: Concentrated stain for cured concrete slabs, brick, plaster, terra cotta, natural stone and may be applied over sealed surfaces (refer to application insturctions).

Not recommended for: Non-porous substrates (e.g. metal, resins, fiberglass) when submerged in water or exposed to severe weather conditions.

Section 2 - Hazards Identification

GHS Ratings:

Inhalation Toxicity Acute Tox. 4 Gases>2500+<=5000ppm, Vapors>10+<=20mg/l,

Dusts&mists>1+<=5mg/l

Skin corrosive 3 Reversible adverse effects in dermal tissue, Draize score: >=

1.5 < 2.3

GHS Hazards

H316 Causes mild skin irritation

H332 Harmful if inhaled

GHS Precautions

P261 Avoid breathing dust/fume/gas/mist/vapours/spray
P271 Use only outdoors or in a well-ventilated area

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P332+P313 If skin irritation occurs: Get medical advice/attention

Signal Word: Warning



SDS for: SCW-0900 Page 1 of 8

Printed: 10/7/2015 at 11:22:50AM

Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
	Inert	40.00% - 50.00%
Water softened	7732-18-5	20.00% - 30.00%
3,6-bis(4-chlorophenyl)-2,5-dihydro-pyrrolo[3,4-c]pyrrole-1,4-dione	84632-65-5	20.00% - 30.00%
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	25265-77-4	1.00% - 5.00%
SILICA AMORPHOUS	7631-86-9	1.00% - 5.00%
2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE	6846-50-0	1.00% - 5.00%
Copper Phthalocyanine	147-14-8	1.00% - 5.00%

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician . Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell. **INGESTION** - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce vomiting.

Notes to Physician: Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Flash Point: > 100 C (>212 F)

LEL: UEL:

Flammable Limits:

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SDS for: SCW-0900 Page 2 of 8

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Inert	Not Established	Not Established	Not Established
Water softened 7732-18-5	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established
3,6-bis(4-chlorophenyl)-2,5-dihydro-pyrrolo[3,4-c]pyrrole-1,4-dione 84632-65-5	None of the components in this product at concentrations greater than 0.1% are listed by IARC; NTP; OSHA or ACGIH as a carcinogen.	None of the components in this product at concentrations greater than 0.1% are listed by IARC; NTP; OSHA or ACGIH as a carcinogen.	Not Established
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE 25265-77-4	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	Not Established

SDS for: SCW-0900 Page 3 of 8

SILICA AMORPHOUS 7631-86-9	Not Established	Not Established	Not Established
2,2,4-TRIMETHYL 1,3- PENTENDIOL DIISPBURYRATE 6846-50-0	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established
Copper Phthalocyanine 147-14-8	TWA 1 mg/m3 Dust and mist.	TWA 1 mg/m3 Dust and mist.	Not Established

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstance:

Explosive Limits: Not Determined

octanol/water):

Decomposition temperature: Not Determined Viscosity: 1100-1300 cPs

Grams VOC less water: 32.52

Odor: Slight Amine

Odor threshold: Not Determined

pH: 9.5 - 10.0

Melting point: Not Determined

Solubility: Not Determined

Flash point: >212°F or >100°C

Flammability: Not Applicable

Partition coefficient (n- Not Determined

Appearance: Liquid

Vapor Pressure: N/A

Vapor Density: 2.1

Specific Density: 1.05 Freezing point: 0°C

Boiling range: 100°C

Evaporation rate: Not Determined

Section 10 - Stability and Reactivity

Stability:

STABLE

Incompatibilities/Condidtions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 12mg/L

Component Toxicity

84632-65-5 3,6-bis(4-chlorophenyl)-2,5-dihydro-pyrrolo[3,4-c]pyrrole-1,4-dione

Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rat) Inhalation LC50: 2,250

mg/m3 (Rat)

25265-77-4 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE

Inhalation LC50: 4 mg/L (Rat)

7631-86-9 SILICA AMORPHOUS

SDS for: SCW-0900 Page 4 of 8 Oral LD50: 5,000 mg/kg (Rat) Inhalation LC50: 2,000 mg/m3 (Rat)

6846-50-0 2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE

Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Guinea Pig) Inhalation LC50: 0

mg/L (Rat)

147-14-8 Copper Phthalocyanine

Dermal LD50: 5,000 mg/kg (Rat)

Primary routes of entry: Inhalation, Skin contact.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS NumberDescription% WeightCarcinogen RatingNoneNo Data Available

Section 12 - Ecological Information

Component Ecotoxicity

Water softened Toxicity of the Products of Biodegradation: The product itself and its products of

degradation are not toxic.

3,6-bis(4-chlorophenyl)-2,5-

dihydro-pyrrolo[3,4-c]pyrrole-1,4-

dione

Toxicity to fish: LC50 >100 mg/l, species: zebra fish

Toxicity to daphnia: EC50 >100 mg/l, species: daph. Mag. straus Toxicity to algae: EC50 >100 mg/l, species: scenedesmus subspicat

Sludge toxicity: EC50 >100 mg/l, species: waste water bacteria

2,2,4-TRIMETHYL 1,3-

PENTENDIOL

MONOISOBUTYRATE

Toxicity
Acute Toxicity

Fish

Product: No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

: 33 mg/l

Aquatic invertebrates

Product No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

147.8 mg/l

Chronic Toxicity

Fish

Product: No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate No data available

Aquatic invertebrates

Product No data available

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate No data available

Mobility in soil: Log Koc - log koc: 1.5 - 2.8

SDS for: SCW-0900 Page 5 of 8

LC-50 (Flathead Minnow, 96h)

EC-50 (Water Flea, 48h):

Results of PBT and vPvB No data available.

assessment:

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate Not fulfilling PBT

(persistent/bioaccumulative/toxic) criteria

Other adverse effects: No data available

SILICA AMORPHOUS Fish Toxicity LC0 (96h) (static) 10000 mg/l (zebra fish) (OECD 203)

Water Flea Toxicity EC50 (24H) 1000 mg/l (Daphnia magna) (OECD 202)

Algae Toxicity EC50 (72h) 10000 mg/l (Scenedesmus subspicatus) (OECD 201)

2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE Toxicity

Acute Toxicity

Fish

Product: NOEC: (Fish, 96h):>=6mg/l (limit of solubility in fresh water)

Aquatic Invertebrates

Product: NOEC: (daphnid, 48h):>=1.46 mg/l (limit of solubility in fresh

water)

Chronic Toxicity

Fish

Product: No data available

Specified substance(s)

Aquatic invertebrates

Product: EC-50 (daphnid, 21 d):>1.3 mg/l (limit of solubility in fresh water)

NOEC: (daphnid, 21 d): 0.7 mg/l

Toxicity to Aquatic Plants

Product: EC-50 (Alga, 72 h):> 7.49 mg/l (limit of solubility in fresh water)

Persistence and degradability

Biodegradation

Product: 70.73% (28 d, Ready Biodegradability: CO2 Evolution Test)

Readily biodegradable, failing 10-d window

Biological Oxygen Demand:

Product: BOD-5 and BOD-20 were not determined because the aqueous

solubility of the test article was below that which is required for these tests.

Chemical Oxygen Demand:

Product: No data available

BOD/COD ratio

Product: No data available

Specified substance(s)

Bioaccumulative potential

Product: Fish, Bioconcentration factor (BCF): 1.95 (Measured)

Fish, Bioconcentration factor (BCF): 183 - 194 (Measured)

SDS for: SCW-0900 Page 6 of 8

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Results of PBT and vPvB

Not fulfilling PBT (persistent/bioaccumulative/toxic)

criteria

assessment:

Other adverse effects: No data available.

Copper Phthalocyanine

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Section 13 - Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

Agency DOT Proper Shipping Name Water Based Paint

UN Number Unregulated **Packing Group**

Hazard Class
Non Hazardous

Section 15 - Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

R2K List

- None

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HEALTH 1 FLAMMABILITY 1 PHYSICAL HAZARD 0 PERSONAL PROTECTION H

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be

SDS for: SCW-0900 Page 7 of 8

Reviewer Revision

Printed: 10/7/2015 at 11:22:50AM

Date Prepared: 10/7/2015

SDS for: SCW-0900 Page 8 of 8