

Section 1 - Chemical Product and Company Information

Product Name: Ornamental Art Gloss White Paint Product Code: OAO-0100

Trade Name: Gloss White Paint

Manufactured by: Smith Paint Products 2200 Paxton Street Harrisburg, PA 17111 (800) 466-8781

Chemtrec 2900 Fairview Park Drive Falls Church, VA 22042-4513 (800) 262-8200

Emergency Hot Line: (800) 424-9300

Product Use: Paint for cured concrete (refer to application insturctions). Not recommended for: Non-porous substrates (e.g. metal, resins, fiberglass) when submerged in water or exposed to severe weather conditions.

Section 2 - Hazards Identification

| <u>GHS Ratings:</u> Carcinogen | 2 | Limited evidence of human or animal carcinogenicity | |
|-----------------------------------|--|---|--|
| <u>GHS Hazards</u> | | | |
| H351 | Suspected of causing cancer | | |
| GHS Precautions | | | |
| P201 | Obtain special instructions before use | | |
| P202 | Do not handle until all safety precautions have been read and understood | | |
| P281 | Use personal protective equipment as required | | |
| P308+P313 | IF exposed or concerned: Get medical advice/attention | | |
| P405 | Store locked up | | |
| P501 | Dispose of contents/container to | | |

Signal Word: Warning



| Section 3 - Composition/Information on Ingredients | | | |
|--|------------|------------------------|--|
| Chemical Name | CAS number | Weight Concentration % | |

| | Inert | 40.00% - 50.00% |
|---|------------|-----------------|
| Water softened | 7732-18-5 | 30.00% - 40.00% |
| TITANIUM DIOXIDE | 13463-67-7 | 10.00% - 20.00% |
| 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE | 25265-77-4 | 1.00% - 5.00% |
| 2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE | 6846-50-0 | 1.00% - 5.00% |

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell. **INGESTION** - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce vomiting.

Notes to Physician: Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Flash Point: > 100 C (>212 F)

LEL:

UEL:

Flammable Limits:

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations. LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas. Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

| Section 8 - Exposure Controls / Personal Protection | | | |
|---|---|--|-----------------------|
| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
| Inert | Not Established | Not Established | Not Established |
| Water softened 7732-18-5 | No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. | Not Established |
| TITANIUM DIOXIDE 13463-67-7 | OSHA PEL TWA (Total Dust) 15 mg/m3 (50 mppcf*) | ACGIH TLV TWA (inhalable particles) 10 mg/m3 | Not Established |
| 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE 25265-77-4 | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | Not Established |
| 2,2,4-TRIMETHYL 1,3- PENTENDIOL DIISPBURYRATE 6846-50-0 | No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. | Not Established |

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstance:

Appearance: Liquid Vapor Pressure: Not Applicable Vapor Density: 2.0 Specific Density: 1.12 Freezing point: 0°C Boiling Point: 100°C Evaporation rate: Not Determined Explosive Limits: Not Determined

Viscosity: 1100 - 1300 cPs

Odor: Slight Amine Odor threshold: Not Determined pH: 9.5 - 10.0 Melting point: Not Determined Solubility: Not Determined Flash point: >212°F or >100°C Flammability: Not Applicable Partition coefficient (n- Not Determined octanol/water): Decomposition temperature: Not Determined Grams VOC less water: 52.07

Section 10 - Stability and Reactivity

Stability: STABLE

Incompatibilities/Condictions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 44mg/L

Component Toxicity

| ווי | | |
|-----|------------|--|
| | 13463-67-7 | TITANIUM DIOXIDE |
| | | Inhalation LC50: 7 mg/L (Rat) |
| | 25265-77-4 | 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE |
| | | Inhalation LC50: 4 mg/L (Rat) |
| | 6846-50-0 | 2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE |
| | | Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Guinea Pig) Inhalation LC50: 0 mg/L (Rat) |
| | | |

Primary routes of entry: Inhalation, Skin contact.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

| <u>CAS Number</u> 13463-67-7 | Description TITANIUM DIOXIDE | <u>% Weight</u> 10 to 20% | Carcinogen Rating TITANIUM DIOXIDE: |
|--|---------------------------------|------------------------------|--|
| Section 12 - Ecological Information | | | |
| Component Ecotoxicity Water softened Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic. | | | |
| TITANIUM DIOXIDE | Ecotoxicity: | | |

| | Persistence and degradability: Readily degradable in the enviroment. | | |
|---|---|-------------------------------|--|
| | Bioaccumulative potential: No additional information. | | |
| | Mobility in soil: No additional information. | | |
| | Other adverse effects: No additional information. | | |
| 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE | Toxicity Acute Toxicity Fish | | |
| | Product: No data available. | | |
| | Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate : 33 mg/l | LC-50 (Flathead Minnow, 96h) | |
| | Aquatic invertebrates Product No data available. | | |
| | Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate 147.8 mg/l | EC-50 (Water Flea, 48h): | |
| | Chronic Toxicity | | |
| | Fish Product: No data available. | | |
| | Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate | No data available | |
| | Aquatic invertebrates Product No data available | | |
| | Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate | No data available | |
| | Mobility in soil: Log Koc - log koc: 1.5 - 2.8 | | |
| | Results of PBT and vPvB No data available. assessment: | | |
| | 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (persistent/bioaccumulative/toxic) criteria | Not fulfilling PBT | |
| | Other adverse effects: No data available | | |
| 2,2,4-TRIMETHYL 1,3- | Toxicity | | |
| PENTENDIOL DIISPBURYRATE | Acute Toxicity | | |
| | Fish Product: NOEC: (Fish, 96h):>=6mg/l (limit of | f solubility in fresh water) | |
| | Aquatic Invertebrates Product: NOEC: (daphnid, 48h):>=1.46 mg/l water) | (limit of solubility in fresh | |

| С | hronic Toxicity | |
|-----|---|---|
| • • | ish Product: | No data available |
| A | pecified substan Aquatic invertebra Product: NOE | |
| | oxicity to Aquatic roduct: | : Plants EC-50 (Alga, 72 h):> 7.49 mg/l (limit of solubility in fresh water) |
| Р | ersistence and c | legradability |
| Р | iodegradation roduct: leadily biodegrac | 70.73% (28 d, Ready Biodegradability: CO2 Evolution Test) lable, failing 10-d window |
| Р | iological Oxyger roduct: olubility of the te | Demand: BOD-5 and BOD-20 were not determined because the aqueous st article was below that which is required for these tests. |
| | chemical Oxygen Product: | Demand: No data available |
| | OD/COD ratio Product: | No data available |
| S | pecified substan | ce(s) |
| | ioaccumulative p roduct: Fish, Bio | potential Fish, Bioconcentration factor (BCF): 1.95 (Measured) concentration factor (BCF): 183 - 194 (Measured) |
| Μ | lobility in soil: | No data available. |
| К | nown or predicte | ed distribution to enviromental compartments |
| cr | Results of PBT ar riteria ssessment: | nd vPvB Not fulfilling PBT (persistent/bioaccumulative/toxic) |
| 0 | other adverse effe | ects: No data available. |

Section 13 - Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

As cited in the IATA Dangerous Goods Handbook:

Section 3.3.1.3: Liquids described in Section 3.3.1.2 with a flash point exceeding 35°C which do not sustain

combustion need not be considered as flammable liquids for the purpose of these Regulations

(b) their fire point accoring to ISO 2592:1973 is greater than 100°C

| DOTWater Based PaintUIATAWater Based PaintUADR/RIDWater Based PaintU | IN Number Packing Group Inregulated Inregulated Inregulated Inregulated | Hazard Class Non Hazardous Non Hazardous Non Hazardous Non Hazardous |
|--|---|--|
|--|---|--|

Section 15 - Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:


13463-67-7 TITANIUM DIOXIDE Carcinogen

R2K List


13463-67-7 TITANIUM DIOXIDE

Section 16 - Other Information

Hazardous Material Information System (HMIS)



National Fire Protection Association (NFPA)



The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Date Prepared: 2/8/2016