

# **Section 1 - Chemical Product and Company Information**

Product Name: Ornamental Art Midnight BluePaint Product Code: OAO-0180

Trade Name: Midnight Blue Paint

Manufactured by: Smith Paint Products 2200 Paxton Street Harrisburg, PA 17111 (800) 466-8781

Chemtrec 2900 Fairview Park Drive Falls Church, VA 22042-4513 (800) 262-8200

Emergency Hot Line: (800) 424-9300

Product Use: Paint for cured concrete (refer to application insturctions). Not recommended for: Non-porous substrates (e.g. metal, resins, fiberglass) when submerged in water or exposed to

severe weather conditions.

# Section 2 - Hazards Identification

GHS Ratings: Carcinogen	2	Limited avidance of human or animal aprainageniaity	
6	2	Limited evidence of human or animal carcinogenicity	
<u>GHS Hazards</u>			
H351	Suspected of ca	using cancer	
GHS Precautions			
P201	Obtain special instructions before use		
P202	Do not handle until all safety precautions have been read and understood		
P281	Use personal protective equipment as required		
P308+P313	IF exposed or co	oncerned: Get medical advice/attention	
P405	Store locked up		
P501	Dispose of conte	ents/container to	

Signal Word: Warning



Section 3 - Composition/Information on Ingredients		
Chemical Name	CAS number	Weight Concentration %

	Inert	40.00% - 50.00%
Water softened	7732-18-5	30.00% - 40.00%
TITANIUM DIOXIDE	13463-67-7	5.00% - 10.00%
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	25265-77-4	1.00% - 5.00%
2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE	6846-50-0	1.00% - 5.00%

# **Section 4 - First Aid Measures**

**INHALATION** - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

**EYE CONTACT** - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

**SKIN CONTACT** - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell. **INGESTION** - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce vomiting.

Notes to Physician: Symptoms may be delayed.

## **Section 5 - Fire Fighting Measures**

Flash Point: > 100 C (>212 F)

LEL:

UEL:

Flammable Limits:

**EXTINGUISHING MEDIA:** Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:** The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

**HAZARDOUS COMBUSTION PRODUCTS:** See section 10 for a list of hazardous decomposition products for this mixture.

**FIRE FIGHTING:** If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

**FIRE FIGHTING EQUIPMENT:** Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

### **Section 6 - Accidental Release Measures**

**SPILL AND LEAK PROCEDURES:** Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

**SMALL SPILLS:** Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations. LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas. Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## Section 7 - Handling and Storage

**HANDLING PRECAUTIONS:** Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

Section 8 - Exposure Controls / Personal Protection			
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Inert	Not Established	Not Established	Not Established
Water softened 7732-18-5	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established
TITANIUM DIOXIDE 13463-67-7	OSHA PEL TWA (Total Dust) 15 mg/m3 (50 mppcf*)	ACGIH TLV TWA (inhalable particles) 10 mg/m3	Not Established
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE 25265-77-4	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	Not Established
2,2,4-TRIMETHYL 1,3- PENTENDIOL DIISPBURYRATE 6846-50-0	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established

## **Section 9 - Physical and Chemical Properties**

This mixture typically exhibits the following properties under normal circumstance:

Appearance: Liquid Vapor Pressure: Not Applicable Vapor Density: 2.0 Specific Density: 1.06 Freezing point: 0°C Boiling Point: 100°C Evaporation rate: Not Determined Explosive Limits: Not Determined

Viscosity: 1100 - 1300 cPs

Odor: Slight Amine Odor threshold: Not Determined pH: 9.5 - 10.0 Melting point: Not Determined Solubility: Not Determined Flash point: >212°F or >100°C Flammability: Not Applicable Partition coefficient (n- Not Determined octanol/water): Decomposition temperature: Not Determined Grams VOC less water: 46.55

# Section 10 - Stability and Reactivity

Stability: STABLE

Incompatibilities/Condictions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

#### Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

Hazardous polymerization will not occur.

### Section 11 - Toxicological Information

#### **Mixture Toxicity**

Inhalation Toxicity LC50: 125mg/L

#### **Component Toxicity**

13463-67-7	TITANIUM DIOXIDE
	Inhalation LC50: 7 mg/L (Rat)
25265-77-4	2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE
	Inhalation LC50: 4 mg/L (Rat)
6846-50-0	2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE
	Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Guinea Pig) Inhalation LC50: 0 mg/L (Rat)

Primary routes of entry: Inhalation, Skin contact.

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS Number 13463-67-7	Description TITANIUM DIOXIDE	<u>% Weight</u> 5 to 10%	Carcinogen Rating TITANIUM DIOXIDE:
Section 12 - Ecological Information			
Component Ecotoxicity Water softened	Toxicity of the Produdegradation are not	0	ne product itself and its products of
TITANIUM DIOXIDE	Ecotoxicity: Fish: LC 50 - o	ther fish - > 1,000 mg/l - 9	96h

Invertebrates: EC 50 - Daphnia magna (water flea) - > 1,000 mg/l - 48h

	Persistence and degradability: Readily degradable in the enviroment.	
	Bioaccumulative potential: No additional information.	
	Mobility in soil: No additional information.	
	Other adverse effects: No additional information.	
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	Toxicity Acute Toxicity Fish	
	Product: No data available.	
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate : 33 mg/l	LC-50 (Flathead Minnow, 96h)
	Aquatic invertebrates Product No data available.	
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate 147.8 mg/l	EC-50 (Water Flea, 48h):
	Chronic Toxicity	
	Fish Product: No data available.	
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	No data available
	Aquatic invertebrates Product No data available	
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	No data available
	Mobility in soil: Log Koc - log koc: 1.5 - 2.8	
	Results of PBT and vPvB No data available. assessment:	
	2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (persistent/bioaccumulative/toxic) criteria	Not fulfilling PBT
	Other adverse effects: No data available	
2,2,4-TRIMETHYL 1,3-	Toxicity	
PENTENDIOL DIISPBURYRATE	Acute Toxicity	
	Fish Product: NOEC: (Fish, 96h):>=6mg/l (limit of	f solubility in fresh water)
	Aquatic Invertebrates Product: NOEC: (daphnid, 48h):>=1.46 mg/l water)	(limit of solubility in fresh

Chronic Toxicity	
Fish Product: No data available	
Specified substance(s) Aquatic invertebrates Product: EC-50 (daphnid, 21 d):>1.3 mg/l (limit of solubility in NOEC: (daphnid, 21 d): 0.7 mg/l	n fresh water)
Toxicity to Aquatic Plants Product: EC-50 (Alga, 72 h):> 7.49 mg/l (limit of solubility in	fresh water)
Persistence and degradability	
Biodegradation Product: 70.73% (28 d, Ready Biodegradability: CO2 Evolut Readily biodegradable, failing 10-d window	ion Test)
Biological Oxygen Demand: Product: BOD-5 and BOD-20 were not determined because solubility of the test article was below that which is required for these	•
Chemical Oxygen Demand: Product: No data available	
BOD/COD ratio Product: No data available	
Specified substance(s)	
Bioaccumulative potential Product: Fish, Bioconcentration factor (BCF): 1.95 (Measured) Fish, Bioconcentration factor (BCF): 183 - 194 (Measured)	ed)
Mobility in soil: No data available.	
Known or predicted distribution to enviromental compartments	
Results of PBT and vPvB Not fulfilling PBT (persistent/bioaccun criteria assessment:	nulative/toxic)
Other adverse effects: No data available.	

# Section 13 - Disposal Considerations

Dispose in accordance with all applicable regulations.

# Section 14 - Transport Information

This material is classified for transport as follows:

As cited in the IATA Dangerous Goods Handbook:

Section 3.3.1.3: Liquids described in Section 3.3.1.2 with a flash point exceeding 35°C which do not sustain

combustion need not be considered as flammable liquids for the purpose of these Regulations

(b) their fire point accoring to ISO 2592:1973 is greater than 100°C

Agency DOTProper Shipping Name Water Based PaintUN Number UnregulatedPacking GIATAWater Based PaintUnregulatedIATAWater Based PaintUnregulatedADR/RIDWater Based PaintUnregulatedIMDGWater Based PaintUnregulated	Froup Hazard Class Non Hazardous Non Hazardous Non Hazardous Non Hazardous Non Hazardous
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------

### **Section 15 - Regulatory Information**

#### State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:


13463-67-7 TITANIUM DIOXIDE Carcinogen

#### R2K List


13463-67-7 TITANIUM DIOXIDE

## **Section 16 - Other Information**

#### Hazardous Material Information System (HMIS)



#### National Fire Protection Association (NFPA)



The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Date Prepared: 2/8/2016