## **Safety Data Sheet**



# **Section 1 - Chemical Product and Company Information**

Product Name: Ornamental Art Copper Green Paint Product Code: OAO-0205

Trade Name: Copper Green Paint

Manufactured by: Chemtrec

Smith Paint Products
2900 Fairview Park Drive
2200 Paxton Street
Falls Church, VA 22042-4513
Harrisburg, PA 17111
(800) 262-8200

Emergency Hot Line: (800) 424-9300

Product Use: Paint for cured concrete (refer to application insturctions).

Not recommended for: Non-porous substrates (e.g. metal, resins, fiberglass) when submerged in water or exposed to severe weather conditions.

#### **Section 2 - Hazards Identification**

**GHS Ratings:** 

(800) 466-8781

Carcinogen 2 Limited evidence of human or animal carcinogenicity

**GHS Hazards** 

H351 Suspected of causing cancer

**GHS Precautions** 

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P281 Use personal protective equipment as required

P308+P313 IF exposed or concerned: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container to ...

Signal Word: Warning



# Section 3 - Composition/Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
---------------	------------	------------------------

	Inert	40.00% - 50.00%
Water softened	7732-18-5	30.00% - 40.00%
TITANIUM DIOXIDE	13463-67-7	10.00% - 20.00%
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	25265-77-4	1.00% - 5.00%
2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE	6846-50-0	1.00% - 5.00%

### **Section 4 - First Aid Measures**

**INHALATION** - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician . Administer oxygen if a qualified operator is available.

**EYE CONTACT** - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

**SKIN CONTACT** - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell. **INGESTION** - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce vomiting.

Notes to Physician: Symptoms may be delayed.

## **Section 5 - Fire Fighting Measures**

Flash Point: > 100 C (>212 F)

LEL: UEL:

#### Flammable Limits:

**EXTINGUISHING MEDIA:** Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:** The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

**HAZARDOUS COMBUSTION PRODUCTS:** See section 10 for a list of hazardous decomposition products for this mixture.

**FIRE FIGHTING:** If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

**FIRE FIGHTING EQUIPMENT:** Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

## **Section 6 - Accidental Release Measures**

**SPILL AND LEAK PROCEDURES:** Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

**SMALL SPILLS:** Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

**LARGE SPILLS:** Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

OAO-0205 Page 2 of 7

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## **Section 7 - Handling and Storage**

**HANDLING PRECAUTIONS:** Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

## **Section 8 - Exposure Controls / Personal Protection**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Inert	Not Established Not Estab		lished Not Established	
Water softened 7732-18-5	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established	
TITANIUM DIOXIDE 13463-67-7	OSHA PEL TWA (Total Dust) 15 mg/m3 (50 mppcf*)	ACGIH TLV TWA (inhalable particles) 10 mg/m3	Not Established	
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE 25265-77-4	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	Not Established	
2,2,4-TRIMETHYL 1,3- PENTENDIOL DIISPBURYRATE 6846-50-0	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established	

# **Section 9 - Physical and Chemical Properties**

This mixture typically exhibits the following properties under normal circumstance:

Appearance: Liquid

Vapor Pressure: Not Applicable

Vapor Density: 2.0 Specific Density: 1.09 Freezing point: 0°C Boiling Point: 100°C

Evaporation rate: Not Determined

Explosive Limits: Not Determined

Autoignition temperature: Not Determined

Viscosity: 1100 - 1300 cPs

**Odor:** Slight Amine

Odor threshold: Not Determined

pH: 9.5 - 10.0

Melting point: Not Determined Solubility: Not Determined

Flash point: >212°F or >100°C Flammability: Not Applicable

Partition coefficient (n- Not Determined

octanol/water):

**Decomposition temperature:** Not Determined

Grams VOC less water: 49.56

## Section 10 - Stability and Reactivity

#### Stability:

**STABLE** 

Incompatibilities/Condidtions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

Hazardous polymerization will not occur.

## Section 11 - Toxicological Information

#### **Mixture Toxicity**

Inhalation Toxicity LC50: 134mg/L

#### **Component Toxicity**

13463-67-7 TITANIUM DIOXIDE

Inhalation LC50: 7 mg/L (Rat)

25265-77-4 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE

Inhalation LC50: 4 mg/L (Rat)

6846-50-0 2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE

Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Guinea Pig) Inhalation LC50: 0

mg/L (Rat)

Primary routes of entry: Inhalation, Skin contact.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

**CAS Number Description** % Weight Carcinogen Rating TITANIUM DIOXIDE 10 to 20% 13463-67-7 TITANIUM DIOXIDE:

# **Section 12 - Ecological Information**

**Component Ecotoxicity** 

Water softened Toxicity of the Products of Biodegradation: The product itself and its products of

degradation are not toxic.

TITANIUM DIOXIDE Ecotoxicity:

Fish: LC 50 - other fish - > 1,000 mg/l - 96h

Invertebrates: EC 50 - Daphnia magna (water flea) - > 1,000 mg/l - 48h

OAO-0205 Reviewer Revision Page 4 of 7

Persistence and degradability:

Readily degradable in the environment.

Bioaccumulative potential: No additional information.

Mobility in soil: No additional information.

Other adverse effects: No additional information.

2,2,4-TRIMETHYL 1,3-PENTENDIOL MONOISOBUTYRATE Toxicity
Acute Toxicity

Fish

Product: No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate LC-50 (Flathead Minnow, 96h)

: 33 mg/l

Aquatic invertebrates

Product No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate EC-50 (Water Flea, 48h):

147.8 mg/l

**Chronic Toxicity** 

Fish

Product: No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate No data available

Aquatic invertebrates

Product No data available

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate No data available

Mobility in soil: Log Koc - log koc: 1.5 - 2.8

Results of PBT and vPvB No data available.

assessment:

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

(persistent/bioaccumulative/toxic) criteria

Other adverse effects: No data available

2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE

Toxicity

**Acute Toxicity** 

Fish

Product: NOEC: (Fish, 96h):>=6mg/l (limit of solubility in fresh water)

Not fulfilling PBT

Aquatic Invertebrates

Product: NOEC: (daphnid, 48h):>=1.46 mg/l (limit of solubility in fresh

water)

OAO-0205 Page 5 of 7

Chronic Toxicity

Fish

Product: No data available

Specified substance(s) Aquatic invertebrates

Product: EC-50 (daphnid, 21 d):>1.3 mg/l (limit of solubility in fresh water)

NOEC: (daphnid, 21 d): 0.7 mg/l

Toxicity to Aquatic Plants

Product: EC-50 (Alga, 72 h):> 7.49 mg/l (limit of solubility in fresh water)

Persistence and degradability

Biodegradation

Product: 70.73% (28 d, Ready Biodegradability: CO2 Evolution Test)

Readily biodegradable, failing 10-d window

Biological Oxygen Demand:

Product: BOD-5 and BOD-20 were not determined because the aqueous solubility of the test article was below that which is required for these tests.

Chemical Oxygen Demand:

Product: No data available

BOD/COD ratio

Product: No data available

Specified substance(s)

Bioaccumulative potential

Product: Fish, Bioconcentration factor (BCF): 1.95 (Measured)

Fish, Bioconcentration factor (BCF): 183 - 194 (Measured)

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Results of PBT and vPvB

Not fulfilling PBT (persistent/bioaccumulative/toxic)

criteria assessment:

Other adverse effects: No data available.

# **Section 13 - Disposal Considerations**

Dispose in accordance with all applicable regulations.

# **Section 14 - Transport Information**

This material is classified for transport as follows:

As cited in the IATA Dangerous Goods Handbook:

Section 3.3.1.3: Liquids described in Section 3.3.1.2 with a flash point exceeding 35°C which do not sustain

OAO-0205 Page 6 of 7

(b) their fire point accoring to ISO 2592:1973 is greater than 100°C

<b>Agency</b>	Proper Shipping Name	<u>UN Number</u> <u>F</u>	acking Group Hazard Class
DOT	Water Based Paint	Unregulated	Non Hazardous
IATA	Water Based Paint	Unregulated	Non Hazardous
ADR/RID	Water Based Paint	Unregulated	Non Hazardous
IMDG	Water Based Paint	Unregulated	Non Hazardous

## **Section 15 - Regulatory Information**

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

13463-67-7 TITANIUM DIOXIDE Carcinogen

#### **R2K List**


13463-67-7 TITANIUM DIOXIDE

#### **Section 16 - Other Information**

#### **Hazardous Material Information System (HMIS)**

# HEALTH 1 FLAMMABILITY 1 PHYSICAL HAZARD PERSONAL PROTECTION H 1 HMIS & NFPA Hazard Rating Legend \* = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH

#### National Fire Protection Association (NFPA)



The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Date Prepared: 2/8/2016