

Section 1 - Chemical Product and Company Information

Product Name: Ornamental Art Dark Desert Rose Paint Product Code: OAO-0290

Trade Name: Dark Desert Rose Paint

Manufactured by: Smith Paint Products 2200 Paxton Street Harrisburg, PA 17111 (800) 466-8781

Chemtrec 2900 Fairview Park Drive Falls Church, VA 22042-4513 (800) 262-8200

Emergency Hot Line: (800) 424-9300

Product Use: Paint for cured concrete (refer to application insturctions). Not recommended for: Non-porous substrates (e.g. metal, resins, fiberglass) when submerged in water or exposed to severe weather conditions.

Section 2 - Hazards Identification

GHS Ratings:			
Carcinogen	2	Limited evidence of human or animal carcinogenicity	
GHS Hazards			
H351	Suspected of causi	ng cancer	
GHS Precautions			
P201	Obtain special instr	uctions before use	
P202	Do not handle until all safety precautions have been read and understood		
P281	Use personal protective equipment as required		
P308+P313	IF exposed or concerned: Get medical advice/attention		
P405	Store locked up		
P501	Dispose of contents	s/container to	

Signal Word: Warning



Section 3 - Composition/Information on Ingredients				
Chemical Name CAS number Weight Concentration %				

	Inert	40.00% - 50.00%
Water softened	7732-18-5	30.00% - 40.00%
TITANIUM DIOXIDE	13463-67-7	5.00% - 10.00%
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	25265-77-4	1.00% - 5.00%
2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE	6846-50-0	1.00% - 5.00%
TRANS RED IO	1309-37-1	1.00% - 5.00%

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell. **INGESTION** - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce vomiting.

Notes to Physician: Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Flash Point: > 100 C (>212 F)

LEL:

UEL:

Flammable Limits:

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations. LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas. Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits		
Inert	Not Established	Not Established	Not Established		
Water softened 7732-18-5	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.			vels greater than or equal 0 0.1% is identified as a carcinogen or potential carcinogen by OSHA.product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by	
TITANIUM DIOXIDE 13463-67-7	OSHA PEL TWA (Total Dust) 15 mg/m3 (50 mppcf*)	ACGIH TLV TWA (inhalable particles) 10 mg/m3	Not Established		
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE 25265-77-4	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	Not Established		
2,2,4-TRIMETHYL 1,3- PENTENDIOLNo component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA.		No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established		

TRANS RED IO	Long-term exposure limit (8-	Long-term exposure limit (8-	Not Established
1309-37-1	hour TWA): OSHA 10 mg/m ³ fume Long-term exposure limit (8- hour TWA): OSHA 15 mg/m ³ total dust Long-term exposure limit (8- hour TWA): OSHA 5 mg/m ³ respirable fraction	hour TWA): ACGIH 5 mg/m³ respirable fraction	

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstance:

Appearance: Liquid	Odor: Slight Amine
Vapor Pressure: Not Applicable	Odor threshold: Not Determined
Vapor Density: 2.0	pH: 9.5 - 10.0
Specific Density: 1.08	Melting point: Not Determined
Freezing point: 0°C	Solubility: Not Determined
Boiling Point: 100°C	Flash point: >212°F or >100°C
Evaporation rate: Not Determined	Flammability: Not Applicable
Explosive Limits: Not Determined	Partition coefficient (n- Not Determined octanol/water):
Autoignition temperature: Not Determined	Decomposition temperature: Not Determined
Viscosity: 1100 - 1300 cPs	Grams VOC less water: 45.39

Section 10 - Stability and Reactivity

Stability:

STABLE

Incompatibilities/Condidtions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 124mg/L

Component Toxicity 13463-67-7	TITANIUM DIOXIDE
	Inhalation LC50: 7 mg/L (Rat)
25265-77-4	2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE Inhalation LC50: 4 mg/L (Rat)
6846-50-0	2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Guinea Pig) Inhalation LC50: 0 mg/L (Rat)

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u> 13463-67-7	Description TITANIUM DIOXIDE	<u>% Weight</u> 5 to 10%	Carcinogen Rating TITANIUM DIOXIDE:			
Section 12 - Ecological Information						
Component Ecotoxicity						
Water softened	loxicity of the Prod degradation are no	-	ne product itself and its products of			
TITANIUM DIOXIDE		Ecotoxicity: Fish: LC 50 - other fish - > 1,000 mg/l - 96h Invertebrates: EC 50 - Daphnia magna (water flea) - > 1,000 mg/l - 48h				
	Persistence and de Readily degrad	gradability: dable in the enviroment.				
	Bioaccumulative po	otential: No additional infor	rmation.			
	Mobility in soil: No	additional information.				
	Other adverse effect	cts: No additional informat	ion.			
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	Toxicity Acute Toxicity Fish Product: N	lo data available.				
	Specified substanc 2,2,4-trimethyl-1,3- : 33 mg/l	e(s) pentanediol monoisobutyra	ate LC-50 (Flathead Minnow, 96h)			
	Aquatic invertebrate Product No da	es ata available.				
	Specified substanc 2,2,4-trimethyl-1,3- 147.8 mg/l	e(s) pentanediol monoisobutyra	ate EC-50 (Water Flea, 48h):			
	Chronic Toxicity					
	Fish Product: N	lo data available.				
	Specified substance 2,2,4-trimethyl-1,3-	e(s) pentanediol monoisobutyra	ate No data available			
	Aquatic invertebrate Product No da	es ata available				
	Specified substance 2,2,4-trimethyl-1,3-	e(s) pentanediol monoisobutyra	ate No data available			
	Mobility in soil:	Log Koc - log koc: 1.5	- 2.8			

	Results of PBT an assessment: 2,2,4-trimethyl-1, (persistent/bioacc	3-pentanediol	•	Not fulfilling PBT
	Other adverse eff	fects: No	data available	
2,2,4-TRIMETHYL 1,3-	Toxicity			
PENTENDIOL DIISPBURYRATE	Acute Toxicity			
	Fish Product:	NOEC: (Fish	, 96h):>=6mg/l (limit of	solubility in fresh water)
	Aquatic Invertebra Product: water)		nnid, 48h):>=1.46 mg/l ((limit of solubility in fresh
	Chronic Toxicity			
	Fish Product:	No data avai	lable	
	Specified substar Aquatic invertebr Product: NO	ates EC-50 (daph	nid, 21 d):>1.3 mg/l (lin 21 d): 0.7 mg/l	nit of solubility in fresh water)
	Toxicity to Aquation Product:		72 h):> 7.49 mg/l (limit	of solubility in fresh water)
	Persistence and degradability			
	Biodegradation Product: Readily biodegrad	•		ity: CO2 Evolution Test)
	Biological Oxyger Product: solubility of the te	BOD-5 and E	3OD-20 were not deterr below that which is req	nined because the aqueous uired for these tests.
	Chemical Oxyger Product:	n Demand: No data avai	lable	
	BOD/COD ratio Product:	No data avai	lable	
	Specified substance(s)			
	Bioaccumulative Product: Fish, Bio	Fish, Biocond	centration factor (BCF): n factor (BCF): 183 - 19	
	Mobility in soil:	No data	available.	
	Known or predicted distribution to enviromental compartments			
	Results of PBT a	nd vPvB	Not fulfilling PBT (pers	istent/bioaccumulative/toxic)

criteria assessment:

Other adverse effects: No data available.

Section 13 - Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

As cited in the IATA Dangerous Goods Handbook:

Section 3.3.1.3: Liquids described in Section 3.3.1.2 with a flash point exceeding 35°C which do not sustain combustion need not be considered as flammable liquids for the purpose of these Regulations

(b) their fire point accoring to ISO 2592:1973 is greater than 100°C

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	Water Based Paint	Unregulated		Non Hazardous
IATA	Water Based Paint	Unregulated		Non Hazardous
ADR/RID	Water Based Paint	Unregulated		Non Hazardous
IMDG	Water Based Paint	Unregulated		Non Hazardous

Section 15 - Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

13463-67-7 TITANIUM DIOXIDE Carcinogen 1309-37-1 TRANS RED IO Mutagen

R2K List

13463-67-7 TITANIUM DIOXIDE 1309-37-1 TRANS RED IO

Section 16 - Other Information

Hazardous Material Information System (HMIS)

1

1

0

н

National Fire Protection Association (NFPA) Flammability Health I nstability Special

The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the

HMIS & NFPA Hazard Rating

* = Chronic Health Hazard

0 = INSIGNIFICANT

Legend

1 = SLIGHT

3 = HIGH

2 = MODERATE

HEALTH

FLAMMABILITY

PHYSICAL HAZARD

PERSONAL PROTECTION

raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Date Prepared: 2/8/2016