

Section 1 - Chemical Product and Company Information

Product Name: Ornamental Art Hollandia Paint Product Code: OAO-0365

Trade Name: Hollandia Paint

Manufactured by: Smith Paint Products 2200 Paxton Street Harrisburg, PA 17111 (800) 466-8781

Chemtrec 2900 Fairview Park Drive Falls Church, VA 22042-4513 (800) 262-8200

Emergency Hot Line: (800) 424-9300

Product Use: Paint for cured concrete (refer to application insturctions).

Not recommended for: Non-porous substrates (e.g. metal, resins, fiberglass) when submerged in water or exposed to severe weather conditions.

Section 2 - Hazards Identification

GHS Ratings:			
Carcinogen	2	Limited evidence of human or animal carcinogenicity	
GHS Hazards			
H351	Suspected of causing cancer		
GHS Precautions			
P201	Obtain special instructions before use		
P202	Do not handle until all safety precautions have been read and understood		
P281	Use personal protective equipment as required		
P308+P313	IF exposed or concerned: Get medical advice/attention		
P405	Store locked up		
P501	Dispose of contents/c	ontainer to	

Signal Word: Warning



Section 3 - Composition/Information on Ingredients				
Chemical Name CAS number Weight Concentration %				

	Inert	40.00% - 50.00%
Water softened	7732-18-5	30.00% - 40.00%
TITANIUM DIOXIDE	13463-67-7	5.00% - 10.00%
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	25265-77-4	1.00% - 5.00%
2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE	6846-50-0	1.00% - 5.00%
DIETHYLENE GLYCOL MONOETHYL ETHER	111-77-3	1.00% - 5.00%

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell. **INGESTION** - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce vomiting.

Notes to Physician: Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Flash Point: > 100 C (>212 F)

LEL:

UEL:

Flammable Limits:

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations. LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas. Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

Section 8 - Exposure Controls / Personal Protection				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Inert	Not Established	Not Established	Not Established	
Water softened 7732-18-5	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established	
TITANIUM DIOXIDE 13463-67-7	OSHA PEL TWA (Total Dust) 15 mg/m3 (50 mppcf*)	ACGIH TLV TWA (inhalable particles) 10 mg/m3	Not Established	
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE 25265-77-4	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	Not Established	
2,2,4-TRIMETHYL 1,3- PENTENDIOL DIISPBURYRATE 6846-50-0	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	Not Established	
DIETHYLENE GLYCOL MONOETHYL ETHER 111-77-3	Not Established	Not Established	Not Established	

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstance:

Appearance: Liquid Vapor Pressure: Not Applicable Vapor Density: 2.0 Specific Density: 1.05 Freezing point: 0°C Boiling Point: 100°C Evaporation rate: Not Determined Explosive Limits: Not Determined

Viscosity: 1100 - 1300 cPs

Odor: Slight Amine Odor threshold: Not Determined pH: 9.5 - 10.0 Melting point: Not Determined Solubility: Not Determined Flash point: >212°F or >100°C Flammability: Not Applicable Partition coefficient (n- Not Determined octanol/water): Decomposition temperature: Not Determined Grams VOC less water: 45.74

Section 10 - Stability and Reactivity

Stability:

STABLE

Incompatibilities/Condictions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 122mg/L

Component Toxicity

•	
13463-67-7	TITANIUM DIOXIDE
	Inhalation LC50: 7 mg/L (Rat)
25265-77-4	2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE
	Inhalation LC50: 4 mg/L (Rat)
6846-50-0	2,2,4-TRIMETHYL 1,3-PENTENDIOL DIISPBURYRATE
	Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Guinea Pig) Inhalation LC50: 0 mg/L (Rat)

Primary routes of entry: Inhalation, Skin contact.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	Description	<u>% Weight</u>	Carcinogen Rating	
13463-67-7	TITANIUM DIOXIDE	5 to 10%	TITANIUM DIOXIDE:	
Section 12 - Ecological Information				

Component Ecotoxicity Water softened

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

TITANIUM DIOXIDE	Ecotoxicity: Fish: LC 50 - other fish - > 1,000 mg/l - 96h Invertebrates: EC 50 - Daphnia magna (water flea) - > 1,000 mg/l - 48h			
	Persistence and degradability: Readily degradable in the enviroment.			
	Bioaccumulative potential: No additional information			
	Mobility in soil: No additional information.			
	Other adverse effects: No additional information.			
2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE	Toxicity Acute Toxicity Fish			
	Product: No data available.			
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate : 33 mg/l	LC-50 (Flathead Minnow, 96h)		
	Aquatic invertebrates Product No data available.			
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate 147.8 mg/l	EC-50 (Water Flea, 48h):		
	Chronic Toxicity			
	Fish Product: No data available.			
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	No data available		
	Aquatic invertebrates Product No data available			
	Specified substance(s) 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	No data available		
	Mobility in soil: Log Koc - log koc: 1.5 - 2.8			
	Results of PBT and vPvB No data available. assessment:			
	2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (persistent/bioaccumulative/toxic) criteria	Not fulfilling PBT		
	Other adverse effects: No data available			
2,2,4-TRIMETHYL 1,3- PENTENDIOL DIISPBURYRATE	Toxicity			
	Acute Toxicity			
	Fish Product: NOEC: (Fish, 96h):>=6mg/l (limit o	f solubility in fresh water)		

Aquatic Invertebra Product: water)	ates NOEC: (daphnid, 48h):>=1.46 mg/l (limit of solubility in fre	esh
Chronic Toxicity		
Fish Product:	No data available	
Specified substan Aquatic invertebr Product: NOI		ı water)
Toxicity to Aquation Product:	: Plants EC-50 (Alga, 72 h):> 7.49 mg/l (limit of solubility in fresh v	vater)
Persistence and c	legradability	
Biodegradation Product: Readily biodegrad	70.73% (28 d, Ready Biodegradability: CO2 Evolution Testable, failing 10-d window	st)
Biological Oxyger Product: solubility of the te	n Demand: BOD-5 and BOD-20 were not determined because the aq st article was below that which is required for these tests.	lueous
Chemical Oxygen Product:	Demand: No data available	
BOD/COD ratio Product:	No data available	
Specified substan	ce(s)	
Bioaccumulative p Product: Fish, Bic	ootential Fish, Bioconcentration factor (BCF): 1.95 (Measured) concentration factor (BCF): 183 - 194 (Measured)	
Mobility in soil:	No data available.	
Known or predicte	ed distribution to enviromental compartments	
Results of PBT ar criteria assessment:	nd vPvB Not fulfilling PBT (persistent/bioaccumulativ	e/toxic)
Other adverse eff	ects: No data available.	

Section 13 - Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

As cited in the IATA Dangerous Goods Handbook:

Section 3.3.1.3: Liquids described in Section 3.3.1.2 with a flash point exceeding 35°C which do not sustain combustion need not be considered as flammable liquids for the purpose of these Regulations

(b) their fire point accoring to ISO 2592:1973 is greater than 100°C

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	Water Based Paint	Unregulated		Non Hazardous
IATA	Water Based Paint	Unregulated		Non Hazardous
ADR/RID	Water Based Paint	Unregulated		Non Hazardous
IMDG	Water Based Paint	Unregulated		Non Hazardous

Section 15 - Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

13463-67-7 TITANIUM DIOXIDE Carcinogen

R2K List

13463-67-7 TITANIUM DIOXIDE


Section 16 - Other Information

Hazardous Material Information System (HMIS)



HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH

National Fire Protection Association (NFPA)



The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Date Prepared: 2/8/2016