

Safety Data Sheet

Section 1 - Chemical Product and Company Information

Product Name: Walnut Product Code: SCA-ML-3100

Trade Name: Walnut Manufactured by: Smith Paint Products 2200 Paxton Street Harrisburg, PA 17111 (800) 466-8781

Chemtrec

2900 Fairview Park Drive Falls Church, VA 22042-4513

(800) 262-8200

Emergency Hot Line: (800) 424-9300

Section 2 - Hazards Identification

GHS Hazards

GHS Precautions

Signal Word:

Section 3 - Composition/Information on Ingredients

| Chemical Name | CAS number | Weight Concentration % | |
|---|------------|------------------------|--|
| | Inert | 40.00% - 50.00% | |
| Water softened | 7732-18-5 | 30.00% - 40.00% | |
| MICA | 12001-26-2 | 5.00% - 10.00% | |
| 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE | 25265-77-4 | 1.00% - 5.00% | |
| TRANS RED IO | 1309-37-1 | 1.00% - 5.00% | |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate | 6846-50-0 | 1.00% - 5.00% | |

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician . Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell. **INGESTION** - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce

Notes to Physician: Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Flash Point: > 100 C (>212 F)

LEL: UEL:

Flammable Limits:

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

Section 8 - Exposure Controls / Personal Protection

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|---|---|---|-----------------------|
| Inert | Not Established | Not Established | Not Established |
| Water softened 7732-18-5 | No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen. | No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen. | Not Established |
| MICA 12001-26-2 | - | TWA: 3 mg/m³ respirable fraction | Not Established |
| 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE 25265-77-4 | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | Not Established |
| TRANS RED IO 1309-37-1 | Long-term exposure limit (8-hour TWA): OSHA 10 mg/m³ fume Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction | Long-term exposure limit (8- hour TWA): ACGIH 5 mg/m³ respirable fraction | Not Established |
| 2,2,4-Trimethyl-1,3- pentanediol diisobutyrate 6846-50-0 | No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA. | No component of this product presents at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. | Not Established |

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstance:

Explosive Limits: Not Determined

Autoignition temperature: 388°C

Viscosity: Not Determined

Appearance: Liquid Specific Density: 1.08 Freezing point: 0°C

Boiling range: 100 - 280°C Evaporation rate: Not Applicable

Vapor Pressure: N/A Vapor Density: 2.0

Partition coefficient (n- Not Determined

octanol/water):

Decomposition temperature: Not Determined

Grams VOC/liter less water 0.23

Odor: Slight Amine

Melting point: Not Determined Solubility: Not Determined Flash point: >212°F,>100°C Flammability: Not Applicable Odor threshold: Not Determined

pH: 9.5 - 10.0

Section 10 - Stability and Reactivity

Stability:

STABLE

Incompatibilities/Condidtions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 2,814mg/L

Component Toxicity

25265-77-4 2,2,4-TRIMETHYL 1,3- PENTENDIOL MONOISOBUTYRATE

Inhalation LC50: 4 mg/L (Rat)

6846-50-0 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate

Oral LD50: 3,200 mg/kg (Rat)

Primary routes of entry: Inhalation, Skin contact.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS Number Description % Weight Carcinogen Rating None No Data Available

Section 12 - Ecological Information

Component Ecotoxicity

Water softened Toxicity of the Products of Biodegradation: The product itself and its products of

degradation are not toxic.

MICA No Data Available

2,2,4-TRIMETHYL 1,3-Toxicity **PENTENDIOL Acute Toxicity**

MONOISOBUTYRATE Fish

> No data available. Product:

SCA-MI -3100 Reviewer Revision Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate LC-50 (Flathead Minnow, 96h)

: 33 mg/l

Aquatic invertebrates

Product No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

147.8 mg/l

Chronic Toxicity

Fish

Product: No data available.

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

No data available

Aquatic invertebrates

Product No data available

Specified substance(s)

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

No data available

Mobility in soil: Log Koc - log koc: 1.5 - 2.8

Results of PBT and vPvB No data available.

assessment:

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate

(persistent/bioaccumulative/toxic) criteria

Not fulfilling PBT

EC-50 (Water Flea, 48h):

Other adverse effects: No data available

2,2,4-Trimethyl-1,3-pentanediol diisobutyrate

Freshwater Fish LC50: > 1.55 mg/L, 96h static (Pimephale

Water Flea

EC5 = 1.46 mg/L, 48h

Persistence and Degradability: Insoluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation: No information available.

Mobility: No information available.

Section 13 - Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

SCA-ML-3100 Reviewer Revision As cited in the IATA Dangerous Goods Handbook:

Section 3.3.1.3: Liquids described in Section 3.3.1.2 with a flash point exceeding 35°C which do not sustain combustion need not be considered as flammable liquids for the purpose of these Regulations

(b) their fire point according to ISO 2592:1973 is greater than 100°C

| Agency | Proper Shipping Name | UN Number | Packing Group | Hazard Class |
|---------|----------------------|-------------|---------------|---------------------|
| ADR/RID | | Unregulated | | Non Hazardous |
| DOT | | Unregulated | | Non Hazardous |
| IATA | | Unregulated | | Non Hazardous |
| IMDG | | Unregulated | | Non Hazardous |

Section 15 - Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

1309-37-1 TRANS RED IO Mutagen

R2K List

12001-26-2 MICA 1309-37-1 TRANS RED IO

Section 16 - Other Information

The material contained in this Safety Data Sheet is based on information supplied to Smith Paint Products by the raw material suppliers of the individual components of this product. Smith Paint Products believes this information is truthful and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Date Prepared: 7/25/2018