

Smith's
Decorative Concrete Products

WATERBORNE POLYURETHANE

Poly-WB

53% Solids Aliphatic Polyurethane Topcoat
Semi-Gloss Finish

Highly Durable

Rolls Easily

Smith's Poly-WB Semi-Gloss
over Smith's Epoxy UCE200
Metallic & Luster

Levels Better

Smith's Poly-WB Semi-Gloss
over Vinyl Chip system

Applied over a primed concrete surface with a CSP-2
Each coat applied at 5 mils (WFT)

Smith's Poly-WB Semi-Gloss
with Smith's WSC-5500 White
over 2 coats of
Smith's Epoxy VCB46P-5500 White

Smith's WSC
Waterborne Solid Color Pigments

Tack Free @ 77°F / 50% Humidity:
Ave: 2 hrs 10 min

Tack Free @ 77°F / 50% Humidity:
Ave: 1 hrs 33 min

Taber Abrasion:
Best: 105 mg loss
Worst: 129 mg loss
Ave: 115 mg loss

Taber Abrasion:
Best: 39 mg loss
Worst: 42 mg loss
Ave: 49 mg loss

Competitor "A"

Smith's Poly WB



2200 Paxton Street • Harrisburg, PA 17111
www.smithpaints.com • 800-466-8781